

Fusion PTZ Camera

4K PAN, TILT, AND ZOOM



PRODUCT FEATURES

Advanced Auto tracking	The Fusion PTZ Camera comes with advanced auto tracking capabilities onboard.
Group Auto framing	Smart Group Auto framing keeps everyone in the frame, ensuring that no one is left out of the conversation. The lossless optical zoom maintains crystal-clear image quality, keeping your online meetings sharp and smooth. Experience seamless and professional video conferencing with intelligent framing and precision zoom.
True 4K Video	The Fusion PTZ Camera offers 4K video, running at frame rates up to 30fps. Its 8.42 MP SONY CMOS Image Sensor is state-of-the-art and ensures high resolution, excellent color, and smooth video in all kinds of situations.
12X Optical Zoom	Enjoy crystal clear video at extreme ranges. Perfect for the largest and most demanding recording environments. 12X Optical Zoom gets you up close and personal while maintaining lossless image quality.
Smooth and Silent PTZ Movement	Pan, Tilt, and Zoom you can rely on. Precision engineering and smart mechanical design results in smooth, silent, and reliable PTZ hardware.

SPECIFICATIONS SHEET

- Zoom: 12x Optical Zoom
- 80.5-degree field of view
- USB Type-C outputs
- Type-C up to 4Kp30 fps

Features	Advanced Autotracking and Group Autoframing
	Presets supported
	Supports WDR, 3D-Noise Reduction functions
	Day/night switch for surveillance market
	1/2.8 inch-high quality, 8.42 MP CMOS Sensor
	Supports POE+: Ethernet cable for DC power
Environmental Data	Working Temperature: -10°C - 50°C
	Working Humidity: ≤80%
Motorized Pan and Tilt	Pan: ±170°
	Tilt: 90° (up) - 30° (down)
	Rotation speed: Pan-0 - 80°/s, Tilt-0 - 60°/s
Connectivity	USB Type-C
Lens	Focal Length: 3.4mm-40.3mm
	Iris: F 1.8-3.6
	Field of View: 80.5° (Far) - 7.6° (Near)
Mount	Camera mount included for wall
Power supply	POE+ (IEEE802.3at)
	DC12V 2A (via Power Adapter)
Dimensions	220mm×190mm×173mm
	Net weight: 1.47 KG